



**NIPPON
PAINT**

KLEANWALL
Fungicidal Solution

Walltron Kleanwall is recommended for highly infested interior and exterior walls to prevent further growth of algae and fungi.

GREEN ASSURED



PRODUCT FEATURES



Enhance Performance of Topcoat



Inhibits the growth of algae and fungi



Economical

APPLICATION AREA:

It can be used on all types of exterior and interior walls that are susceptible to algal and fungal growth. It can be used on both old or new construction.

TECHNICAL DETAILS

Dilution: Ready to use (No dilution)

Coverage:



WALLTRON KLEANWALL

9.3 - 10.2 sq.m/coat.

Coverage depends on porosity of substrate.





**NIPPON
PAINT**

KLEANWALL
Fungicidal Solution

HOW TO APPLY

Surface Preparation:



- Clean the surface till it is free from dust, grease and flaking paint.
- Any unstable paint, algae and fungi on the wall to be removed, by using high-pressure wash or coir brush.
- Apply one coat of Kleanwall with brush and allow drying for minimum 4-6 hrs.
- After complete drying apply second coat of the Kleanwall,
- After an interval of 4-6 hrs apply primer followed by Nippon emulsion paint.

Precautions:

- Stir well and strain before use.
- Do not use on wet surfaces or when it rains.
- Do not dispose of excess material over natural vegetation.
- Do not thin.
- Avoid painting when the temperature is below 10°C. Painting is not recommended if the moisture content and alkalinity of the walls is high.

Disclaimer:

The information contained in this Technical Data Sheet is based on laboratory tests and practical experience and is provided in good faith to the best of our current knowledge. However, no warranty, express or implied, is given regarding the accuracy, reliability, or completeness of this information. Due to the variety of materials, substrates, site conditions, and methods of application beyond our control, the company expressly disclaims any liability for loss or damage resulting from improper use of the product or reliance on the information provided herein. It is the responsibility of the customer or end user to ensure the product's suitability and compatibility for the intended application by conducting appropriate testing or sampling. For specific recommendations or further technical support, please consult our technical representatives.

SAFETY AND ENVIRONMENT

During Painting:

Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning:

Wash all the tools with water immediately after application.

Safety Instructions:

In the case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint from skin, use soap and water or appropriate cleanser. May be harmful if swallowed. In case of ingestion seek immediate medical attention. In the event of spillage, contain and collect spilt paint by using sand or earth.

Storage:

Store paint in a cool, dry and well ventilated place away from heat sources, flammables or direct sunlight. Keep container tightly closed in a secure, upright position. Do not store near food, drink or animal feed. Keep out of reach of children. Do not dispose of unwanted paint into drains, water sources or open sewers.

Environment:

Does not contain any added lead, mercury or chromium compounds.

Shelf Life:

1 Year from the date of manufacture in original tightly closed container.

